




Technical Data Sheet

for
HRMA



general data

<i>item</i>	split-duct-tee HRMA 32/32-30°, HRMA 40/40-90°, HRMA 50/50-30°, HRMA 50/50-90°
<i>description</i>	for branch off from occupied PE-HD ducts
<i>optional</i>	
<i>package unit</i>	6 pcs.

technical data

quality	value	unit
<i>material</i>	PolyVenylChlorid - Unplastinized PVC-U	
<i>dimension</i>	32/32-30°: d1 = 32; d2 = 32; L = 261;	mm
	40/40-90°: d1 = 40; d2 = 40; L = 261;	mm
	50/50-30°: d1 = 50; d2 = 50; L = 261;	mm
	50/50-90°: d1 = 50; d2 = 50; L = 261;	mm
<i>pressing operation clamp on case</i>	min. 1550	N
<i>tensile strength</i>	32/32-30°: min. 1300	N
	40/40-90°: min. 1300	N
	50/50-30°: min. 1500	N
	50/50-90°: min. 1500	N
<i>pressure</i>	0,5 / 30	bar / min

**The production and the supervision are controlled by a quality system
following DIN EN ISO 9001:2000**

editor: ZM; 31.05.2010

release: MK; 01.06.2010

Page 1 / 1

gabo Systemtechnik GmbH • Am Schaidweg 7 • 94559 Niederwinkling
phone +49 (0) 9962-950 200 • fax +49 (0) 9962-950 202 / 203