


	Technical Data Sheet for DSM permanent	
---	---	---

general data	
<i>item</i>	straight connector permanent DSM 7; DSM 10; DSM 12; DSM 14
<i>description</i>	straight connector to connect gabocom-speedpipe with the same diameter, blow in pressure up to 15 bar, tension proof, removable, suitable for direct buried
<i>optional</i>	
<i>package unit</i>	50 pcs. (Ø7 and Ø10); 25 pcs. (Ø12 and Ø14)

technical data		
quality	value	unit
<i>material</i>	Polyoxymethylen POM	
<i>dimension</i>	DSM 7 p: d = 7; L = 31 DSM 10 p: d = 10; L = 40 DSM 12 p: d = 12; L = 46 DSM 14 p: d = 14; L = 46	mm
<i>pressure</i>	0,5 / 30	bar / min
<i>burst pressure</i>	min. 30	bar
<i>tensile strength</i>	DSM 7 p: min. 200 DSM 10 p: min. 400 DSM 12 p: min. 450 DSM 14 p: min. 500	N

The production and the supervision are controlled by a quality system following DIN EN ISO 9001:2000
--

editor: ZM; 31.05.2010	release: MK; 01.06.2010	Page 1 / 1
gabo Systemtechnik GmbH • Am Schaidweg 7 • 94559 Niederwinkling phone +49 (0) 9962-950 200 • fax +49 (0) 9962-950 202 / 203		